

Thermoquiet® Acoustic Test Ratings;

Floor/Wall/Ceiling - ASTM 2179-03- Delta (Δ) IIC 20

Floor/ Ceiling - ASTM E-90-04 E413 – 04

Floor /Ceiling - ASTM 492-04 / ASTM E989-06 - IIC68

Core Slab Only- ASTM492 -04 / ASTM E989-06 - IIC- 49dB

Thermoquiet® Fire Test Rating;

Certified Fire Retardant - Class A-1 ASTM E84 / GB 8410* – 2006

*(Standard Number: GB 8410-2006 -Replacing Standard :)

GB 8410-1994 Flammability of automotive & interior materials

Thermoquiet® Product Specifications;

TQ100B35 Thermoquite- 100 sq ft (Retail Display case- 9 Rolls) Acoustic /Thermal underlayment
Roll Size - 3.2mm x 48” x 25’ Class A-1 Fire Rated

Roll Weight- 4.5lbs **Case Weight (9) - 55lbs** **Pallet weight (36) - 250lbs**

TQ250B35 Thermoquite- 250 sq ft - (Commercial roll- 4 per case) Acoustic /Thermal underlayment
Roll Size- 3.2mm x 48” x 62.5’ Class A-1 Fire Rated

Roll Weight- 12lbs **Case Weight (4) - 62lbs** **Pallet Weight (16) - 270lbs**

TQ500B35 Thermoquite- 500Sq ft - (Commercial- single roll) Acoustic /Thermal underlayment
Roll Size - 3.2mm x 48” x 125’ Class A-1 Fire Rated

Roll Weight- 24lbs **Gaylord/ Pallet weight (6) – 225lbs**