


Design Number AMV/ICF 180-01
AMVIC INCORPORATED

Amvic Insulated Concrete Forms
ASTM E119-11a
ULC / CAN S101-07

Fire Rating Only - Load Rating Not Within The Scope Of This Listing
Assembly Rating - 3 Hours



1. **CONCRETE:** Pour normal weight concrete (density typically between 145-155 pcf) having a minimum 28 MPa (4,000 psi) nominal compressive strength into the forming system (Item 2).

2. **CERTIFIED MANUFACTURER:** Amvic Incorporated

CERTIFIED PRODUCT: Amvic Insulated Concrete Forms (ICF)

FORMING SYSTEM: The Amvic ICF forming system consists of Type 2 (CAN/ULC S701) or Type II (ASTM C578) molded expanded polystyrene (EPS) foam panels with embedded high density

polypropylene ties that come preassembled as blocks and are produced in nominal concrete core widths of 6 inch (152mm), 8 inch (203 mm), 10 inch (254 mm), and 12 inch (305 mm) widths. The Amvic ICF forming system are produced in 48 inches length x 16 inches height (1220 mm x 410 mm) for 6 inch and 8 inch concrete cores, and are produced in 48 inches length (1220 mm) x 24 inches height (610 mm) for 10 inch and 12 inch concrete cores. All Amvic ICF products have an EPS panel thickness of 2.5 inches. The top and

bottom of the EPS panels have an interlocking system which aligns the forms together as they are stacked together. Amvic ICF systems have high density polypropylene ties spaced at 6 inches on center in the cavity of the ICF that include flanges acting as furring strips for mechanical fastening.

3. SHEATHING, GYPSUM: Use minimum 1/2-inch (12.7mm) thick gypsum board, applied vertically to the interior face of the forming system (Item 2) when minimum 15-minute thermal barrier is required to separate the building's interior from forming system (Item 2). Gypsum board shall be fastened with 1-1/2 inch length Type "W" bugle head gypsum that penetrate the form tie (Item 4). Space screws a minimum 12 inches on center vertically and 16 inches horizontally on the forming system (Item 2) wall. A minimum of one layer of joint compound to be applied to joints and screw heads.

4. POLYPROPYLENE FORM TIES: Each 48 inches (1220 mm) of length, Amvic ICF have eight high density polypropylene ties. The polypropylene ties are spaced nominally 6 inches (152 mm) on center. The polypropylene ties are open to allow the flow around of concrete, and to allow seating for the placement of horizontal and vertical rebar placement.

5. STEEL REINFORCEMENT (Optional): Place the steel reinforcement before filling the forming system with concrete (Item 1). The rebar used is to be designed and placed per the applicable code requirements and approved by a registered design professional the appropriate authorities having jurisdiction.

6. EXTERIOR FINISHES: (Not shown and not required) When desired, apply to the exterior side of the forming system (Item 2) wall assembly without diminishing the assembly rating: any Exterior Insulation Finish System (EIFS), any exterior stucco, brick or brick veneer, stone or stone veneer, cultured stone and siding made from vinyl, aluminum, wood, or steel.

Apply exterior finishes in accordance with the manufacturer's instructions.

7. WALL ASSEMBLY: Use the forming system (Item 2) wall assembly as either an interior or exterior wall. Cover interior walls with sheathing (Item 3), where required, on both sides of the forming system (Item 2). Only cover exterior walls with sheathing (Item 3) on the interior side, where required, of forming system (Item 2). Fire rating applied to forming system (Item 2) wall assembly from exterior side.