



**NOTES:**

1. ALL FASTENING MATERIALS SHALL BE STAINLESS STEEL OR GALVANIZED
2. SLEWED ANCHOR RODS SHALL BE INSTALLED FOLLOWING INSTALLATION OF THE STRAIGHT ANCHOR RODS

LEDGER BOARD FASTENED TO ICF WALL W/ ADHESIVE ANCHOR RODS @ 6" C/C SPACING. ALTERNATE B/W STRAIGHT AND SKEWED, EMBEDDED 4" (102mm) INTO CONCRETE

WOOD JOISTS AND DECKING AS SPECIFIED ON ENGINEERING DRAWINGS (MAX. JOIST SPAN 12' (3.6m))

SKEWED ANCHOR ROD, 1/2" (13mm) C/W BEVELED WASHERS, PLACE RODS AT CENTER OF LEDGER BOARD

STRAIGHT ANCHOR ROD, 3/4" (19mm), PROVIDE BACKING NUT AND WASHER BEHIND LEDGER BOARD, TACK WELDED TO ANCHOR ROD, STAGGER RODS BETWEEN TOP & BOTTOM OF LEDGER BOARD

# WOOD DECK ATTACHMENT TO EXISTING 8" R22 ICF WALL W/ BRICK



7 October 2020